

**LASERMARK® Laser Level Instruments**

Top quality products for over 130 years.

*Technical Specifications*

<b>Laser Diode:</b>	635nm
<b>Horizontal Accuracy:</b>	±1/8-in @ 100-ft (±3.0mm@30m)
<b>Vertical Accuracy:</b>	±1/8-in @ 100-ft (±3.0mm@30m)
<b>Range:</b>	Up to 2000 ft (610m) dia.
<b>Leveling Type:</b>	Pendulum Self-Leveling ±5°
<b>Warranty:</b>	
LM1000	One-Year
LM2000	Two-Year
<b>Environment:</b> Built for all-weather general construction needs (IPX4). Operating Temperature 22°F to 120° (-6°C to 49°C)	
<b>Power:</b> Rechargeable Ni-MH cartridge pack provides 12+ hours use.	



## LM1000/2000 Automatic Self-Leveling Pendulum Dual-Beam Rotary Lasers

The Job Demands Precision. You Demand Performance. The New LM1000 and LM2000 Both Deliver.

### LM1000

Horizontal/Vertical Automatic Self-Leveling Pendulum Dual-Beam Rotary Laser. Range up to 1000-ft.



Cat# 57-RC1000

### LM2000

Horizontal/Vertical Automatic Self-Leveling Pendulum Dual-Beam Rotary Laser with Down Plumb Beam. Range up to 2000-ft.

◀ **Compensator Locking Mechanism** Secures the Compensator for Transporting and Lay-Down Mode



LM2000 Shown

### LM2000 "High Powered" Diode

For the contractor who needs optimum visibility and versatility, the LM2000 is the laser of choice. Its bright red beam and variable rotation speed offer the flexibility of use with or without a detector for interior and outdoor work.

**LM1000/LM2000 Packages**— All include hard-shell carrying case and manual.



LM1000 Standard Package  
57-LM1000



LM2000 Standard Package  
57-LM2000



LM2000 Interior Package  
57-LM2000P



Electronic Detector

Ni-MH Battery Pack/Charger

Target

V-Mount

Remote



**Scanning Feature** Preset Angles of 0°, 10°, 45°, 90°, and 180° to Increase Beam Visibility



**Variable Speed Rotation** for Maximum Visibility in any Light Condition— 0, 150, 300, and 600 RPM



**Clock-wise and CCW Head Positioning** for Fast and Easy Alignment in Vertical/Horizontal Applications



**Dual Beams**-Horizontal Beam and Up Plumb Beam



**Automatic / Manual Mode**



**Anti-Drift System** to Signal Operator When Unit is Moved Out of Position



**Low Battery Indicator** So You Don't Run Out of Power at the Wrong Time



**Heavy Duty Glass Enclosed Beacon** and Durable Sealed Housing is Water and Dust-Proof (IPX4) to Ensure Years of Dependable Operation



**Pro Grade** - Gravity Driven Stainless Steel Bearing Pendulum

### LM2000 (Only)



**Three 635nm Beams**— Horizontal/Vertical Beam, Plumb Up and Plumb Down



**Back Lit Leveling Bubble** for Laydown/Vertical Jobs