

LASERMARK® Laser Level Instruments

Top quality products for over 130 years.

**LM30 Series
Manual-Leveling
Dual-Beam Rotary
Lasers**

One person, one button leveling, plumbing, and alignment. Two speed rotation (150-600 RPM) plus spot mode, short and long sweep modes, and LED low battery indication. Protected level vials prevent damage and shield vials from the sun to prevent misread.



- Protected, shaded level vials prevent damage and shield vials from the sun to prevent misread
- Remote Ready.



Technical Specifications

Laser Diode:	635nm
Accuracy:	±1/4-in @ 100-ft (±6mm@30m)
Range:	Up to 200 ft (60m) indoor diameter; up to 800 ft (244m) outdoor diameter with optional laser detector
Leveling Type:	Manual Two Screw
Sensitivity:	5 minute level vial, 10 minute plumb vial
Warranty:	One-Year
Environment:	Built for all-weather general construction needs (IPX4). Operating Temperature 22°F to 120° (-6°C to 49°C)
Power:	Three (3) "C" cell Alkaline batteries provides 60± hours continue use

- One Person, One Button Operation**
- Variable Speed 360° Rotation** (150-600 RPM) for Maximum Visibility in Any Light Condition
- Spot Mode** for 90° Point to Point
- Short and Long Sweep Mode** Create Laser "Chalkline" to Increase Beam Visibility
- Low Battery Indicator** So You Don't Run Out of Power at the Wrong Time
- Built-in Trivet**— with 5/8" x 11 Thread Tripod Mount. Lay Unit on Its Back for Vertical Applications
- Dual Beam Rotary Head** with "Point and Shoot" Sweep

LM30 Packages— All include instruction manual.

LM30 Standard Package 57-LM30		
LM30 Detector Package 57-LM30D		
LM30 Interior Package 57-LM30I		
LM30 Interior/Detector Package 57-LM30DUI		
LM30 Complete Packages 57-LM30PKG		
57-LM30E-3		

