



Dissolved Oxygen TRACER

Dissolved Oxygen Tracer Order Code 1761

DO Sensor Module Order Code 1762

- Oxygen level displayed as % Saturation from 0 to 200.0% or Concentration from 0 to 20.00 ppm (mg/L)
- Adjustable Altitude Compensation (0-20,000 ft in 1,000 ft increments)
- Adjustable Salinity Compensation from 0 to 50 ppt
- Memory stores up to 25 data sets with DO and Temperature reading
- Self-calibration on power up; Data Hold, Auto power off, Low battery indicator
- Optional 3 ft (1m) or 16 ft (5m) extension cable
- Complete with DO electrode, protective sensor cap, spare membrane cap, electrolyte, four 1.5V SR44W batteries, and 48" (1.2m) neckstrap

Electronic

Description	Range	Resolution	Accuracy
DO (sat. mode)	0 to 200.0%	0.1%	±2% FS
DO (conc. mode)	0 to 20.00 ppm (mg/L)	0.01 ppm (mg/L)	0.4 ppm (mg/L)
Temp.	32 to 122°F (0 to 50°C)	0.1°F/°C	±1.8°F (1°C)
Dimensions	1.4 x 6.9 x 1.6" (36x176x41 mm)		

Accessories

DO Membrane Kit Order Code 1761M
(6 screw-on membranes and solution)

Weighted Stand w/Sample Cups (5) Order Code 1746

Sample Cups w/caps (24) Order Code 1745

DO Extension Cable (1 meters) Order Code 1763

DO Extension Cable (5 meters) Order Code 1764



Code 1764



Code 1761M

Code 1746