



Waterproof!

## pH Pocket Testers

Model	pH 10	pH 20
Waterproof	5-0103	5-0104
Range	-1.0 to 15.0 pH extended range	
Resolution	0.1 pH	0.01 pH
Accuracy	±0.1 pH	±0.01 pH
Calibration	Select up to 3 points (4.0, 7.0, 10.0)	
Operating Temperature	32 to 122°F; 0 to 50°C	
Temperature Compensation	Automatic (ATC) 0 to 50°C	
Special Functions	On/Off or Auto-Off after 8.5 min.; HOLD; CALibrate; CONfirm	
Power & Battery Life	Four 1.5 V alkaline cell batteries (supplied), 500 hours use	
Replacement Electrode	5-0097	
Size (LxWxH)	8.5"L x 2.4"W x 2.5"H (boxed) 6.5"L x 1.5" diameter (unit)	
Shipping	NH (1)	

## Standardized pH Buffer Solutions

For use in calibration of pH meters. Available in 120 mL (-J) and 500 mL (-L) sizes.

pH Value	Code
4.00	2866
7.0	2881
10.00	2896

## Conductivity/TDS Solutions

Value
74 μmohs/cm, 52 ppm Order Code 6416-L
718 μmohs/cm, 503 ppm Order Code 6417-L
1,413 μmohs/cm, 989 ppm Order Code 6354-L
1 μmohs = μS

