

## ASTM PRECISION THERMOMETERS

- Manufactured to ASTM specifications and certified to MIST standards at 5 points.
- Mercury filled, yellow back glass. Each thermometer is individually calibrated against MIST (USA) standards. A Report of Calibration is provided for each thermometer, outlining traceability, tests and temperature corrections. Ideal for use in quality control laboratories and where ISO 9000 standards are in place. Thermometers are individually serialized.

We Offer a Full Line of ASTM and ASTM Partial Immersion Precision Thermometers. Please order by ASTM number.

Item #	Range	Division	Accuracy	Length	Immersion
62C	-38 to 2°C	0.1 °	0.1°C	15 inches	Total
63C	-8 to 32°C	0.1 °	0.1°C	15 inches	Total
64C	25 to 55°C	0.1 °	0.1°C	15 inches	Total
65C	50 to 80°C	0.1 °	0.1°C	15 inches	Total
66C	75 to 105°C	0.1 °	0.1°C	15 inches	Total
67C	95 to 155°C	0.2 °	0.2°C	15 inches	Total
68C	145 to 205°C	0.2 °	0.2°C	15 inches	Total
69C	195 to 305°C	0.5 °	0.5°C	15 inches	Total
70C	295 to 405°C	0.5 °	0.5°C	15 inches	Total
62F	-36 to 35°F	0.2 °	0.2°F	15 inches	Total
63F	18 to 89°F	0.2 °	0.2°F	15 inches	Total
64F	77 to 131°F	0.2 °	0.2°F	15 inches	Total
65F	122 to 176°F	0.2 °	0.2°F	15 inches	Total
66F	167 to 221°F	0.2 °	0.2°F	15 inches	Total
67F	203 to 311°F	0.5 °	0.5°F	15 inches	Total
68F	293 to 401°F	0.5 °	0.5°F	15 inches	Total
69F	383 to 581°F	1 °	1°F	15 inches	Total
70F	503 to 761°F	1 °	1°F	15 inches	Total