



INDUSTRIAL BI - METAL 75MM (3") DUAL CASE DIAL THERMOMETER

- Stainless steel case and stem.
- Polycarbonate lens.
- External recalibration feature.
- 12.7 mm (1/2") NPT threaded connection. These dial thermometers feature stainless steel construction, polycarbonate lens. Connecting nut with 12.7mm (1/2") NPT threaded connection ideal for laboratory and industrial use. Adjustment feature allows for thermometer recalibration. For correct temperature reading, stem must be immersed at least 50 mm (2") in liquids and 100 mm (4") in gases.

Custom ranges, styles and Stem length available in quantity.

Item #	Range	Range	Division	Division	Dial Size	Stem Length	Immersion
21600	-20 to 120 °C	0 to 250 °F	2 °C	2 °F	75 mm	62 mm	50mm (2")
21605	0 to 50 °C	25 to 125 °F	1 °C	1 °F	75 mm	62 mm	50mm (2")
21610	10 to 150 °C	50 to 300 °F	1 °C	2 °F	75 mm	62 mm	50mm (2")
21615	10 to 260 °C	50 to 500 °F	5 °C	5 °F	75 mm	62 mm	50mm (2")
21620	-20 to 120 °C	0 to 250 °F	2 °C	2 °F	75 mm	106 mm	50mm (2")
21625	0 to 50 °C	25 to 125 °F	1 °C	1 °F	75 mm	106 mm	50mm (2")
21630	10 to 150 °C	50 to 300 °F	1 °C	2 °F	75 mm	106 mm	50mm (2")
21635	10 to 260 °C	50 to 500 °F	5 °C	5 °F	75 mm	106 mm	50mm (2")
21640	-40 to 50 °C	-40 to 120 °F	2 °C	2 °F	75 mm	106 mm	50mm (2")
21645	-20 to 120 °C	0 to 250 °F	1 °C	2 °F	75 mm	150 mm	50mm (2")
21650	0 to 50 °C	25 to 125 °F	1 °C	1 °F	75 mm	150 mm	50mm (2")
21655	10 to 150 °C	50 to 300 °F	1 °C	2 °F	75 mm	150 mm	50mm (2")
21660	10 to 260 °C	50 to 500 °F	5 °C	5 °F	75 mm	150 mm	50mm (2")
21665	60 to 400 °C	150 to 750 °F	5 °C	10 °F	75 mm	150 mm	50mm (2")
21670	-40 to 50 °C	-40 to 120 °F	2 °C	2 °F	75 mm	150 mm	50mm (2")
21675	-20 to 120 °C	0 to 250 °F	1 °C	2 °F	75 mm	225 mm	50mm (2")
21680	0 to 50 °C	25 to 125 °F	1 °C	1 °F	75 mm	225 mm	50mm (2")
21685	10 to 150 °C	50 to 300 °F	1 °C	2 °F	75 mm	225 mm	50mm (2")
21690	10 to 260 °C	50 to 500 °F	5 °C	5 °F	75 mm	225 mm	50mm (2")
21695	60 to 400 °C	150 to 750 °F	5 °C	10 °F	75 mm	225 mm	50mm (2")
21700	-20 to 120 °C	0 to 250 °F	1 °C	2 °F	75 mm	305 mm	50mm (2")
21710	0 to 50 °C	25 to 125 °F	1 °C	1 °F	75 mm	305 mm	50mm (2")
21715	10 to 150 °C	50 to 300 °F	1 °C	2 °F	75 mm	305 mm	50mm (2")
21720	10 to 260 °C	50 to 500 °F	5 °C	5 °F	75 mm	305 mm	50mm (2")
21725	60 to 400 °C	150 to 750 °F	5 °C	10 °F	75 mm	305 mm	50mm (2")