

## Enviro-Safe®; Pocket Thermometer



Non-Toxic, Non-Hazardous & Biodegradable.

Enviro-Safe® thermometers replace mercury thermometers and give you the same accuracy without any hazards.

Market leading Enviro-Safe® liquid is 100% non-toxic, non-hazardous, and biodegradable. As if that is not enough, Enviro-Safe® thermometers are also made from lead free glass!

Each unit comes with individual serial numbers (except pocket size and 200mm) and a Statement of Accuracy indicating accuracy traceable to NIST and DKD. These thermometers are made in the USA by H-B Instrument Company - an ISO 9001:2000 company. Thermometer should be stored at a 15° angle minimum.

### Required in these GLOBE protocols

- Air and Water Temperature.
- Relative Humidity.
- Salinity.
- Soil Particle Size.
- Calibration of Other Instruments.

Item #	Item Name	Range	Division	Accuracy	Length
20565	Closed Metal Case	-10 to 110°C	1 °	1°	160 mm
20570	Closed Metal Case	-5 to 50°C	0.5 °	0.5°	160 mm
20560	Closed Metal Case	0 to 220°F	2 °	2°	160 mm
20575	Closed Metal Case	20 to 120°F	1 °	1°	160 mm
20568	Window Metal Case	-10 to 110°C	1 °	1°	160 mm
20572	Window Metal Case	-5 to 50°C	0.5 °	0.5°	160 mm
20562	Window Metal Case	0 to 220°F	2 °	2°	160 mm
20578	Window Metal Case	20 to 120°F	1 °	1°	160 mm
20564	Closed Plastic Case	-10 to 110°C	1 °	1°	160 mm
20574	Closed Plastic Case	-5 to 50°C	0.5 °	0.5°	160 mm
20559	Closed Plastic Case	0 to 220°F	2 °	2°	160 mm
20579	Closed Plastic Case	20 to 120°F	1 °	1°	160 mm
20563	Window Plastic Case	-10 to 110°C	1 °	1°	160 mm
20573	Window Plastic Case	-5 to 50°C	0.5 °	0.5°	160 mm
20558	Window Plastic Case	0 to 220°F	2 °	2°	160 mm
20577	Window Plastic Case	20 to 120°F	1 °	1°	160 mm
20585	Aluminum Duplex Case	-10 to 110°C	1 °	1°	160 mm
20590	Aluminum Duplex Case	-5 to 50°C	0.5 °	0.5°	160 mm
20580	Aluminum Duplex Case	0 to 220°F	2 °	2°	160 mm
20595	Aluminum Duplex Case	20 to 120°F	1 °	1°	160 mm
20568B	Window Nickel-Plated Brass Case	-10 to 110°C	1 °	1°	160 mm
20572B	Window Nickel-Plated Brass Case	-5 to 50°C	0.5 °	0.5°	160 mm
20562B	Window Nickel-Plated Brass Case	0 to 220°F	2 °	2°	160 mm
20578B	Window Nickel-Plated Brass Case	20 to 120°F	1 °	1°	160 mm