



## Double - Safe™ Thermometer

Non-Toxic, Non-Hazardous & Biodegradable.

Double - Safe™ thermometers are the same as Easy-Read® thermometers in that they feature the same black Enviro-Safe® liquid and same yellow back lead free glass, but Double - Safe™ thermometers also feature Teflon® coating making the thermometer less sensitive to breakage. In the event that the thermometer does break, the liquid in the thermometer and the glass itself are contained within the Teflon®. This reduces the hazards of mercury and sample contamination.

Each unit comes with individual serial numbers and a Statement of Accuracy indicating accuracy traceable to NIST (USA) and DKD (Europe).

Item #	Range	Division	Accuracy	Immersion	Length
30591T	-10 to 110°C	1 °	1°	50mm (2")	200 mm
30592T	-10 to 110°C	1 °	1°	Total	200 mm
30593T	-10 to 150°C	1 °	1°	50mm (2")	200 mm
			1.5° above 105°		
30594T	-10 to 150°C	1 °	1°	Total	200 mm
			1.5° above 105°		
30597T	20 to 230°F	2 °	2°	50mm (2")	200 mm
30596T	20 to 230°F	2 °	2°	Total	200 mm
30599T	20 to 300°F	2 °	2°	50mm (2")	200 mm
30598T	20 to 300°F	2 °	2°	Total	200 mm
30505T	-20 to 110°C	1 °	1°	76mm (3")	305 mm
30500T	-20 to 110°C	1 °	1°	Total	305 mm
30515T	-20 to 150°C	1 °	1°	76mm (3")	305 mm
			1.5° above 105°		
30510T	-20 to 150°C	1 °	1°	Total	305 mm
			1.5° above 105°		
30535T	0 to 230°F	2 °	2°	76mm (3")	305 mm
30530T	0 to 230°F	2 °	2°	Total	305 mm
30545T	0 to 300°F	2 °	2°	76mm (3")	305 mm
			3° above 221°		
30540T	0 to 300°F	2 °	2°	Total	305 mm
			3° above 221°		