



## MERCURY ARMORED LABORATORY THERMOMETER

- Mercury filled, yellow back glass.
- Permanently fused markings.
- Nickel-plated brass armor protects thermometer.
- Available with Teflon® coating - add "T" to the end of the part number. These thermometers meet all requirements for physical dimensions and accuracy of ANSI/SAMA Z236.1-1983. Each thermometer is individually calibrated against equipment whose calibration is traceable to NIST (USA) Thermometer should be stored at a 15° angle minimum.

Item #	Range	Division	Accuracy	Length	Immersion
20120A	-30 to 50°C	1 °	1°	305 mm	76mm (3")
20140A	-20 to 110°C	1 °	1°	305 mm	76mm (3")
20150A	-20 to 150°C	1 °	1°	305 mm	76mm (3")
20161A	-10 to 260°C	1 °	1° to 105°C 1.5° above 105°C 2° above 200°C	405 mm	76mm (3")
20170A	-10 to 300°C	1 °	1° to 105°C 1.5° above 105°C 2° above 200°C	405 mm	76mm (3")
20180A	-10 to 400°C	2 °	2° to 105°C 3° above 105°C 4° above 200°C	405 mm	76mm (3")
20160A	0 to 205°C	1 °	1° to 105°C 1.5° above 105°C	305 mm	76mm (3")
20280A	-30 to 120°F	1 °	1°	305 mm	76mm (3")
20300A	0 to 230°F	2 °	1°	305 mm	76mm (3")
20220A	0 to 230°F	2 °	1°	305 mm	76mm (3")
20310A	0 to 300°F	2 °	1°	305 mm	76mm (3")
20321A	20 to 500°F	2 °	2° to 221°F 3° above 221°F 4° above 392°F	405 mm	76mm (3")
20330A	20 to 600°F	2 °	2° to 221°F 3° above 221°F 4° above 392°F	405 mm	76mm (3")
20340A	20 to 750°F	5 °	10° above 600°F 5°F to 600°F	405 mm	76mm (3")