



MERCURY DUAL SCALE THERMOMETER

- Mercury filled, yellow or white back glass.
- Permanently fused markings.
- Dual scale °C and °F. These thermometers have accuracy equivalent to the accuracy requirements of ANSI/SAMA Z236.1-1983, where ranges are specified. Each thermometer is individually calibrated against equipment whose calibration is traceable to NIST (USA) and DKD (Europe). Thermometer should be stored at a 15° angle minimum.

| Item # | Range | Range | Division | Division | Length | Immersion | Back Glass |
|--------|---------------|--------------|----------|----------|--------|-----------|------------|
| 20145W | -20 to 110 °C | 0 to 230 °F | 1 °C | 2 °F | 305 mm | 76mm (3") | White |
| 20065W | -20 to 110 °C | 0 to 230 °F | 1 °C | 2 °F | 305 mm | Total | White |
| 20155W | -20 to 150 °C | 0 to 300 °F | 1 °C | 2 °F | 305 mm | 76mm (3") | White |
| 20075W | -20 to 150 °C | 0 to 300 °F | 1 °C | 2 °F | 305 mm | Total | White |
| 20165W | -10 to 260 °C | 20 to 500 °F | 1 °C | 2 °F | 405 mm | 76mm (3") | White |
| 20085W | -10 to 260 °C | 20 to 500 °F | 1 °C | 2 °F | 405 mm | Total | White |
| 20102W | -10 to 400 °C | 20 to 750 °F | 2 °C | 5 °F | 405 mm | 76mm (3") | White |
| 20101W | -10 to 400 °C | 20 to 750 °F | 2 °C | 5 °F | 405 mm | Total | White |
| 20145 | -20 to 110 °C | 0 to 230 °F | 1 °C | 2 °F | 305 mm | 76mm (3") | Yellow |
| 20065 | -20 to 110 °C | 0 to 230 °F | 1 °C | 2 °F | 305 mm | Total | Yellow |
| 20155 | -20 to 150 °C | 0 to 300 °F | 1 °C | 2 °F | 305 mm | 76mm (3") | Yellow |
| 20075 | -20 to 150 °C | 0 to 300 °F | 1 °C | 2 °F | 305 mm | Total | Yellow |
| 20165 | -10 to 260 °C | 20 to 500 °F | 1 °C | 2 °F | 405 mm | 76mm (3") | Yellow |
| 20085 | -10 to 260 °C | 20 to 500 °F | 1 °C | 2 °F | 405 mm | Total | Yellow |
| 20102 | -10 to 400 °C | 20 to 750 °F | 2 °C | 5 °F | 405 mm | 76mm (3") | Yellow |
| 20101 | -10 to 400 °C | 20 to 750 °F | 2 °C | 5 °F | 405 mm | Total | Yellow |