



MERCURY FRACTIONAL DEGREE THERMOMETER

- Mercury filled, yellow back glass.
- Permanently fused markings.
- Unique serial numbers. These thermometers meet all requirements for physical dimensions and accuracy of ANSI/SAMA Z236.1-1983. Each thermometer is individually calibrated against equipment whose calibration is traceable to NIST (USA) and DKD (Europe). Thermometer should be stored at a 15° angle minimum.

Item #	Range	Division	Accuracy	Length	Immersion
20375	-1 to 51°C	0.1 °	± 1° full scale	460 mm	76mm (3")
20370	-1 to 51°C	0.1 °	± 0.3° full scale	460 mm	Total
20395	-1 to 101°C	0.1 °	± 1° full scale	610 mm	76mm (3")
20440	-1 to 101°C	0.1 °	± 0.3° full scale	610 mm	Total
20425	-1 to 201°C	0.2 °	± 1° to 100°C ± 1.5° above 100°C	610 mm	76mm (3")
20420	-1 to 201°C	0.2 °	± 0.4° to 100°C ± 0.5° above 100°C	610 mm	Total
20475	30 to 124°F	0.2 °	± 2° full scale	460 mm	76mm (3")
20470	30 to 124°F	0.2 °	± 0.5° full scale	460 mm	Total
20495	30 to 214°F	0.2 °	± 2° full scale	610 mm	76mm (3")
20490	30 to 214°F	0.2 °	± 0.5° full scale	610 mm	Total
20497	30 to 394°F	0.5 °	± 2° to 212°F ± 3° above 212°F	610 mm	76mm (3")
20493	30 to 394°F	0.5 °	± 1° to 212°F ± 2° above 212°F	610 mm	Total