



RED SPIRIT GENERAL PURPOSE LABORATORY THERMOMETER

- Red spirit filled, white back glass.
- Permanently fused markings.
- Individually packaged in Safety-Pak® packaging. These thermometers have accuracy equivalent to the accuracy requirements of ANSI/SAMA Z236.1-1983, where ranges are specified. Each thermometer is individually calibrated against equipment whose calibration is traceable to NIST (USA) and DKD (Europe). Thermometer should be stored at a 15° angle minimum.

Item #	Range	Division	Accuracy	Length	Immersion	Back Glass
20771	-35 to 50°C	1 °	1.5°	305 mm	76mm (3")	White
20772	-35 to 50°C	1 °	1°	305 mm	Total	White
20795	-20 to 110°C	1 °	1.5°	305 mm	76mm (3")	White
20790	-20 to 110°C	1 °	1°	305 mm	Total	White
20805	-20 to 150°C	1 °	1.5°	305 mm	76mm (3")	White
20800	-20 to 150°C	1 °	1°	305 mm	Total	White
20765	0 to 230°F	2 °	3°	305 mm	76mm (3")	White
20760	0 to 230°F	2 °	2°	305 mm	Total	White
20775	0 to 300°F	2 °	3°	305 mm	76mm (3")	White
20770	0 to 300°F	2 °	2°	305 mm	Total	White
20755	-40 to 120°F	2 °	3°	305 mm	76mm (3")	White
20750	-40 to 120°F	2 °	2°	305 mm	Total	White