



RED SPIRIT TEFLON®; COATED SAFETY THERMOMETER

- Red spirit filled, white back glass.
 - Permanently fused markings. These thermometers meet all requirements for physical dimensions of ANSI/SAMA Z236.1-1983. Each thermometer is individually calibrated against equipment whose calibration is traceable to NIST (USA) and DKD (Europe). Teflon® coating helps prevent liquid and glass contamination if thermometer is broken.
- Thermometer should be stored at a 15° angle minimum.

Item #	Range	Division	Accuracy	Length	Immersion
20795T	-20 to 110°C	1 °	1.5°	305 mm	76mm (3")
20790T	-20 to 110°C	1 °	1°	305 mm	Total
20805T	-20 to 150°C	1 °	1.5°	305 mm	76mm (3")
20800T	-20 to 150°C	1 °	1°	305 mm	Total
20160ST	-10 to 200°C	1 °	2°	305 mm	76mm (3")
20765T	0 to 230°F	2 °	3°	305 mm	76mm (3")
20775T	0 to 300°F	2 °	3°	305 mm	76mm (3")
20791T	-10 to 110°C	1 °	1°	203 mm	50mm (2")
20792T	-10 to 110°C	1 °	1°	203 mm	Total
20793T	-10 to 150°C	1 °	1°	203 mm	50mm (2")
20794T	-10 to 150°C	1 °	1°	203 mm	Total